
Made in /Germany Tasttechnologie [Clamping technology] Spanntechnologie

Quick setting with the clamping bolts: move each single bolt without clamping screw into the slide block of the machine table and position the bolt by hand as a stopper at the workpiece. Tighten the clamping bolt and it automatically helps you to position the workpiece.

Flexible for diverse workpiece shapes: no matter if round, oval, quadratical or even pentagonal - with the help of the clamping bolts, you can clamp all forms.







Safely fixed: the clamping screws are added from above. They clamp the workpiece powerfully and securely. A soft exchangeable brass ring avoids damages or scratches at the workpiece.

Drill-through: there is not much disturbing space under the workpiece - no clamping jaws, no base, nothing is disturbing when you drill-through your workpiece with diverse divisions of pitch circles.

The small disturbing contour enables multi-purpose machining even at places which you normally hardly reach.



Clamping bolt system FlexiClamp

Build your own clamping system!

Full flexibility thanks to the modular principle

New, incredibly fast and individual application: FlexiClamp

Assemble your FlexiClamp clamping system with the parts you need for your machining!

The FlexiClamp bolts are a modern combination of an aluminum body and hardened steel surfaces. The bolts are available in heights of 50 and 80 mm.

The bolts are positioned and fastened using a centric screw with a hexagonal wrench while the bolt is stationary - without any undesired twisting.

You can reach any position on the machine table with the help of the transvers T-slot bar:







-66-

Spanntechnologie |

Probing technology

Clamping technology

-67-

Tasttechnologie | Spanntechnologie

Tasttechnologie [Clamping technology] Spanntechnologie Tasttechnologie [Clamping technology] Spanntechnologie



FlexiClamp is also suitable for series production, since the workpiece can be changed in just a few simple steps using the bearing clamping screw:









Decide which screw you need:



Art.No. 003S01000 Standard screw for small to medium-sized series: minimized interfering contours thanks to the very flat screw head.



Art.No. 003S02000 Bearing clamping screw also for large series: Faster workpiece changes due to the innovative contour of the bearing screw head.

Decide which clamping height you need:

Stable extension of the clamping height by 20 or 40 mm through a rigid extension with the same clamping screw length:





Extension 20 mm Art.No. 003S00Z11



Clamping bolt height 50 mm Art.No. 003S00050





Clamping bolt height 80 mm Art.No. 003S00080









Slide block

10 - 18 mm

Clamping ring (for bearing Clamping ring standard clamping srew) Art.No. 003S00Z22

Transvers T-slot bar Art.No. 003S00Z21

Art.No. 003S00Z40

Order data:

Article No.	Description
003S01050	FlexiClamp Set clamping bolt M8 height 50 mm + clamping screw standard
003S01080	FlexiClamp Set clamping bolt M8 height 80 mm + clamping screw standard
003S02050	FlexiClamp Set clamping bolt M8 height 50 mm + bearing clamping screw
003S02080	FlexiClamp Set clamping bolt M8 height 80 mm + bearing clamping screw
003S00050	FlexiClamp clamping bolt M8 height 50 mm
003S00080	FlexiClamp clamping bolt M8 height 80 mm
003S01000	FlexiClamp clamping screw standard 5-25 mm
003S02000	FlexiClamp bearing clamping screw 5-25 mm
003S00Z11	FlexiClamp clamping bolt extension +20mm
003S00Z12	FlexiClamp clamping bolt extension +40mm
003S00Z21	FlexiClamp clamping ring standard
003S00Z22	FlexiClamp clamping ring for bearing clamping screw
003S00Z40	FlexiClamp transvers T-slot bar 14 mm (for suitable T-slot distances 63, 100 and 125 mm)
002080028	Slide block M8 x 10
002140301	Slide block M8 x 12
002140327	Slide block M8 x 14
002153460	Slide block M8 x 16
002153478	Slide block M8 x 18

Made in Germany

-68--69Clamping bolts

Tasttechnologie [Clamping technology] Spanntechnologi

Clamping bolts

Conventional steel design



Clamping bolt 50 mm with thread M10 oder M12






Clamping bolt 100 mm with exchangeable threaded bolt



Clamping bolt 150 mm with exchangeable threaded bolt



- 1 clamping bolt
- 2 spring washer
- 3 clamping screw
- 4 clamping ring
- 5 threaded bolt

Type:

Flexible clamping tool for direct clamping on the machine table with direct fixation in the Tslot. Precise tolerance classes guarantee parallel clamping to the machine table. For the bolts with length 100 mm and 150 mm, exchangeable threaded bolts are available. The clamping ring prevents a damage of the workpiece.

Almost all types of flat workpieces can be clamped powerfully and precisely with these clamping bolts. The standard clamping range is 8-40 mm. With the clamping screws (available as spare part) it can be widened to a maximum of 87 mm.

Scope of delivery for height 50 mm:

Clamping bolts with fixed thread, ring & clamping screw with clamping ring

Article No.	Description	Height	Thread
003000050	Clamping bolt	50 mm	M10
003M12050	Clamping bolt	50 mm	M12





Scope of delivery for height 100 mm/150 mm:

Clamping bolts, threaded bolt M10, ring & clamping ring with clamping screw

Article No.	Description	Height	Thread
003000100	Clamping bolt	100 mm	M10
003000150	Clamping bolt	150 mm	M10

Spare parts for clamping bolts

Article No.	Description	Thread
003000Z00	Washer	-
003000Z02	Clamping ring	-
003000Z01	Clamping screw	8 mm - 40 mm
003000Z03	Clamping screw	40 mm - 67 mm
003000Z04	Clamping screw	65 mm - 87 mm
003000M10	Threaded bolt	M10
003000M12	Threaded bolt	M12
003000M14	Threaded bolt	M14
003000M16	Threaded bolt	M16



Set of clamping bolts

Delivery includes:

3 pcs. clamping bolts length 50 or 100, 3 pcs. clamping screw 40-67, 3 pcs. clamping screw 65-87, 1 pcs. The set is in a high-quality wooden case.

Article No.	Description	Height	Thread
003990050	Clamping bolt set	50 mm	M10
003990100	Clamping bolt set	100 mm	M10







Probing technology

-70-

Spanntechnologie |

Probing technology

Tasttechnologie

Spanntechnologie